


L'analyse de données matricielles dans une base de données géospatiale: L'approche PostGIS WKT Raster

Pierre Racine

Professionnel de recherche
Centre d'étude de la forêt
Département des sciences
du bois et de la forêt
Université Laval



Centre de recherche en géomatique
Octobre 2010



What is a spatial database?

- DBMS with native support for the geometry type

- Relations Normalisation
- Standard Query Language (SQL)
- Transactions & Rules
- Security & Backup
- SQL Functions & Operators
(`intersect()`, `within()`, `area()`,
`=`, `&&`, etc...)



shapefile		spatial DB	
properties		districts	
shape	owner	geometry	id
polygon	Jean	polygon	AB12
polygon	Pierre	polygon	CF34
polygon	Marc	polygon	RT43
polygon	Jean	polygon	RE42
...

```
SELECT area(geometry), owner FROM properties, districts  
WHERE intersect(properties.geometry, districts.geometry) and district.id = "AB12"
```


- What is the area — and who is the owner — of properties located in district AB12?

- IBM DB2 Spatial Extender, Informix Spatial DataBlade, Oracle Spatial, PostgreSQL/PostGIS, ESRI's ArcSDE, Intergraph's GeoMedia
- What about raster?

elevation	
raster	rid
raster	RE42
...	...

Introducing PostGIS WKT Raster

- Support for rasters in the PostGIS spatial database
 - RASTER is a new native base type like the PostGIS GEOMETRY type
 - Implemented very much like and as easy to use as the GEOMETRY type
 - One row = one raster
 - One table = one coverage
 - Integrated as much as possible with the GEOMETRY type
 - SQL API easy to learn for usual PostGIS users
 - Full raster/vector analysis capacity taking nodata value into account.
 - Seamless when possible.
 - First release with future PostGIS 2.0
- Development Team
 - Current: Jorge Arevalo, Pierre Racine, Mateusz Loskot, Regina & Leo Obe
 - Past: Sandro Santilli, David Zwarg
- Founding
 - Steve Cumming through a Canada Foundation for Innovation grant
 - Deimos Space, Cadcorp, Michigan Tech Research Institute, Azavea, OSGeo



Chapter 13 on
WKT Raster


Some Open Source Geospatial Software Background

- PostGIS
 - First open source spatial database.
 - Advantageously comparable to the vector part of Oracle Spatial.
 - Developed by Refraction Research (Victoria Canada) and many other contributors since 2001.
 - Used world wide in thousands of installations for the storage, manipulation, analysis and publishing of vector data.
- GDAL/OGR
 - Geospatial Data Abstraction Library.
 - Abstracts raster and vector file formats into a single API used by many software products (open and not open source).
 - Mainly developed since 1998 by Frank Warmerdam (former employe of PCI in Ontario) and many other contributors.
- MapServer
 - Most used and most powerful multilayer rasterizer of geospatial information for webGIS. Used by thousands of web sites around the world.
 - Now mainly developed by MapGears in Chicoutimi.

The Context

The Canadian Spatial Data Foundry

- A web site for researchers in **forestry, ecology and environment**
- Doing **buffer analysis** over **HUGE raster and vector datasets** (covering the extent of Canada)



geom	obsID	cutProp	meanTemp	elevation	etc...
polygon	1	75.2	20.3	450.2	...
polygon	2	26.3	15.5	467.3	...
polygon	3	56.8	17.5	564.8	...
polygon	4	69.2	10.4	390.2	...
...	

Strategies for Implementing the Base Buffering Process

We need code for...	A	B	C
• vector storage & manipulation	database	database	database
• raster storage & manipulation	outside database	database (non-native support)	database (native support)
• analysis processes	specific homemade application	specific homemade application	database

Strategy C (implementing raster as a native type into PostGIS) is a more **elegant and generic solution** answering many more GIS problems

Raster in the Database Requirements

(actually PostGIS WKT Raster features...)


- 1. Support for georeferenced, multiband, multiresolution and tiled raster coverages**
 - Efficient storage of non-rectangular coverages
 - Support for nodata value and numerous pixeltypes
- 2. SQL operators and functions for raster manipulation and analysis**
- 3. SQL operators and functions working seamlessly on raster and vector data**
 - Lossless conversion between raster and vector
- 4. Easy import/export of rasters from/to the filesystem**
- 5. Registration (in the database) of metadata for rasters staying outside the database**

1) Georeferenced, Multiband, Multiresolution and Tiled Coverages

- Georeferenced
 - Each tile/raster is georeferenced
 - Support for rotation (or skew)
- Multiband
 - Support for band with different pixeltypes in the same raster
 - 1BB, 8BSI, 8BUI, 16BSI, 16BUI, 32BSI, 32BUI, 32BF, 64BF
 - Full supports for nodata values (one per band)
 - No real limit on number of band
- Tiled
 - No real distinction between a tile and a raster
 - No real limit on size
 - 1 GB per tile, 32 TB per coverage (table)
 - Rasters are compressed (by PostgreSQL)
 - Support for non-rectangular tiled coverage
- Multiresolution (or overviews) are stored in different tables
- List of raster columns available in a `raster_columns` table similar to the `geometry_columns` table



e.g. SRTM Coverage for Canada



[2) SQL Operators and Functions for Raster Manipulation and Analysis]

implemented, being implemented, planned

- All indexing operators: <<, &<, <<|, &<|, &&, &>, >>, |&>, |>>, ~=, @, ~
- Get and set raster properties: width(), height(), upperleft(), setupperleft(), pixelsize(), setpixelsize(), skew(), setskew(), numbands(), hasband()
- Get and set raster band properties: bandpixeltype(), bandnodatavalue(), setbandnodatavalue(), bandhasnodatavalue(), setbandhasnodatavalue(), bandpath(), bandisnodata(), setbandpath()
- Get and set pixel values: value(), setvalue(), values(), setvalues(), reclass(), getstats(), etc...
- Creation: makeemptyraster(), addband(), addrastercolumn(), etc...
- Transformation: resample(), etc...
- Conversion: toimage(), tojpeg(), totiff(), tokml(), etc...

Simple Examples

- SQL

```
SELECT rid, rast, ST_UpperLeftX(rast), ST_UpperLeftY(rast)  
FROM mytable
```

- PL/pgSQL

```
CREATE OR REPLACE FUNCTION ST_DeleteBand(rast raster, band int)  
RETURNS raster AS $$  
DECLARE  
    numband int := ST_NumBands(rast);  
    newrast raster := ST_MakeEmptyRaster(rast);  
BEGIN  
    FOR b IN 1..numband LOOP  
        IF b != band THEN  
            newrast := ST_AddBand(newrast, rast, b, NULL);  
        END IF;  
    END LOOP;  
    RETURN newrast;  
END;  
$$ LANGUAGE 'plpgsql';
```

3) SQL Operators and Functions Working Seamlessly on Raster and Vector

The time is past when we wanted to work on raster data differently than on vector data!


We just want to work on COVERAGES!

(in whatever format they are: vector, raster, TIN, point cloud, etc...)


- Seamless raster versions of existing geometry functions: `srid()`, `setsrid()`, `convexhull()`, `envelope()`, `isempty()`, `union()`, `area()`, `is valid()`, `centroid()`, `transform()`, `rotate()`, `scale()`, `translate()`, etc...
- Easy raster to vector conversion functions: `dumpaspolygons()`, `polygon()`, `pixelaspolygon()`, `pixelaspolygons()`, etc...
- Easy vector to raster conversion functions: `asraster()`, `toraster()`, `interpolate()`, etc...
- Major vector-like analysis functions working with rasters: `intersection()`, `intersects()`, `within()`, `contains()`, `overlaps()`, etc...
- Major raster-like analysis functions working with vectors: `mapalgebra()`, `clip()`, etc...

3 b) Lossless Conversion Between Vector and Raster Coverages

- Categorical rasters layers convert well to vector layers
 - one variable converts to one column
 - groups together pixels of same value
 - contiguous or not
 - continuous raster layers do not convert as well
- Vector layers do not convert well to raster layers
 - each attribute (e.g. type) must be converted to one raster
 - no support for nominal values (e.g. “M34”)
 - global values (area) lose their meaning
 - overlaps are lost
 - resolution must be high to match vector precision
 - features lose their unique identities
 - reconversion to the original vector is very difficult or impossible



landcover




area


We need a better way to convert vector layers to rasters without destroying objects' identities

3 b) Lossless Conversion Between Vector and Raster Layers


- In a **vector layer**, each object has **its own identity**




landcover			
geometry	type	mapsheet	area
polygon	4	M34	13.34
polygon	3	M33	15.43
polygon	7	M33	10.56
polygon	9	M34	24.54
polygon	5	M33	23.43
polygon	2	M32	12.34
...



- In a **raster layer converted** from a vector layer, each object should also **conserve its own identity**



landcover			
raster	type	mapsheet	area
raster	4	M34	13.34
raster	3	M33	15.43
raster	7	M33	10.56
raster	9	M34	24.54
raster	5	M33	23.43
raster	2	M32	12.34
...





- Each “raster object” has **its own georeference**
- Black pixels are “**nodata values**”
- Like vectors, raster objects may or may not overlap
- Raster algorithms can be used on the whole layer after a “**blend**” of the objects into a single raster

Rasters become just another way to store geographic features in a more expressive vector object-oriented-like style

ST_Intersection (implemented)


- The goal is to be able to do **overlay operation on coverages** the **same way** we are used to do them on vector coverage but **without worrying if data are stored in vector format or raster format**.



```

SELECT obsid,(gv).geom, (gv).val, ST_Area((gv).geom) as area FROM (
  SELECT ST_Intersection(ST_Buffer(observ.geom, 1000), cover.rast ) as gv,
  obsid, ctype
  FROM observation, cover
  WHERE ST_Intersects(ST_Buffer(observation.geom, 1000), cover.rast )
) foo
  
```

- ST_Intersects takes nodata value into account.
- Great simplification of applications concepts and graphical user interfaces
- See the tutorial on the WKT Raster wiki...



[ST_MapAlgebra (being implemented)]

- Generate a **new raster**, pixel by pixel, as a the **result of an expression** involving one, two or more rasters
 - **One input and two input rasters versions**
 - Resulting **extent** can be the same as the **first raster**, the **second raster**, the **intersection** or the **union** of both
 - **Misaligned and different resolution rasters** are automatically **resampled** to first or second raster
 - **Absent values** (or nodata values) are replaced with **NULL** or a provided value (so we can refer to them in expressions)
 - Resulting **pixeltype** can be specified
 - Will allow referring to **surrounding or neighbor tile pixels** values for focal & zonal functions. i.e. 'rast2[-1, -1]'
 - Expressions are evaluated by the PostgreSQL SQL engine so that users can use their own PL/pgSQL functions
 - Will also allow passing geometries and values in place of raster for a seamless integration with vector data

$$[a] = [b] + [c]$$

7	6
2	4

4	2
1	3

3	4
1	1

[-1,1]	[0,1]	[1,1]
[-1,0]	[0,0]	[1,0]
[-1,-1]	[0,-1]	[1,-1]

ST_MapAlgebra (being implemented)

- **Example 1:** Reclassifying pixel values (one raster version)

- `SELECT ST_MapAlgebra(rast, 'CASE WHEN rast < 0 THEN 0`

- `ELSE rast`
`END')`

- `FROM elevation`

-4	2	0
-1	-4	2
-2	0	1

0	2	0
0	0	2
0	0	1

- **Example 2:** Computing the mean + some personnal adjustment (two rasters version)

- `SELECT ST_MapAlgebra(elev1.rast, elev2.rast, 'rast1 + rast2) / 2 +`

- `MyAdjustment(rast1, rast2)', '32BF', 'INTERSECTION')`

- `FROM elev1, elev2 WHERE ST_Intersects(elev1.rast, elev2.rast)`

- You can also **intersect** or **merge** rasters, create raster **aggregates**, and **many funny things!**

-10	0	0	
-4	0	-6	2
-1	-4.5	0	1
-2	0	1	

[4) Easy Import/Export of Raster From/To the Filesystem]


4) Easy Import/Export of Raster From/To the Filesystem



- Import is done with **gdal2wktraster.py**
 - Very similar to PostGIS **shp2pgsql**
 - Batch import, production of **overviews** and creation of **tiling and index**
 - Can import **many file formats** (thanks to GDAL)
 - Example:
 - `gdal2wktraster.py -r "c:/temp/mytiffolder/*.tif" -t mytable -s 4326 -k 50x50 -I > c:\temp\mytif.sql`
 - `psql -f c:\temp\mytif.sql testdb`
- Export is done using the **GDAL WKT Raster driver**

5) Registration of Metadata for Rasters Staying Outside the Database

- Provide faster loading and export of files for desktop application
- Provide faster access for web applications (JPEGs)
- Avoid useless database backup of large datasets not requiring edition
- Avoid importation (copy) of large datasets into the database
- All functions should eventually work seamlessly with out-db raster
- Data read/write with GDAL (many formats)
- Eventual possibility to convert out-db raster to in-db raster and hence, to load rasters in the DB using SQL
 - CREATE TABLE outraster AS
`SELECT ST_MakeRegisteredRaster('c:/temp/mytiff/*.tif')`
 - CREATE TABLE inraster AS
`SELECT ST_MakeBandInDB(rast, band) FROM outraster`



A Complete Framework for Light GIS Application Development


- **GIS in the Database:** A complete SQL geospatial API working as seamlessly as possible on any type of coverage

- Vector, raster, TIN, point cloud, etc...
- Implicitly tiled and spatially indexed
- Use SQL: The most used, most easy and **most minimalist though complete** language to work with data in general. Easily extensible (PL/pgSQL)
- Keep the **processes close to the data** where the data should be: in a database
- **DBMS client-server architecture** good for desktop and web applications, single and multi-users

- More lightweight applications

- All the (geo)processing can be done in the database
- Desktop and web applications become simple **SQL query builders and data display**

Desktop or Web Application
(query building & display)






Spatial Database
(geoprocessing)

Introducing WKT Raster "Raster Objects"

- Rasters created by converting geometries coverage become raster becomes **vector like "raster objects"**.
- Like vector geometries, raster objects:
 - are **independent** from each others
 - have their own **localisation** (or georeference)
 - can **overlap**
 - can **change location independently**
 - can represent **individual objects** with their own **identity**
- Moreover, raster objects can be used to model real life objects better represented as **small fields** (like **fires** or **fuzzy objects**).
- Very **new type of GIS object**

Raster Objects VS Other GIS Objects

- Point and Line Coverages
- Polygon Coverages
 - Objects represent a **constant surface with an identity and properties** (like an object in a OO context)
- New Raster Object Coverages
 - Constant Raster Objects (categorical)
 - Objects represent a **constant surface with an identity and properties** (like a feature or an object)
 - Better modelled as **polygon**, but modelled as raster because they are **better processed using existing raster algorithms** (eg. landcover, basin)
 - E.g.: **land use; land cover**; traditional raster objects that should overlap but can't because they are in raster format (ex. **buffers, animal territories**)
 - Variable Raster Objects (field)
 - Objects represent a **variable field** that have an **identity and properties**
 - Generally modelised as a **unique raster** and **difficult to model as polygons**
 - E.g.: **fire, fuzzy objects (lakes, land cover, forest stands, soil), area of influence, animal territories**
- Traditional Raster Coverages
 - Represent a **variable field** with **different values (no unique identity or other properties)**
 - E.g.: **elevation, climate, etc...**



Comparison with Oracle GeoRaster



Oracle GeoRaster

- Stored as a one to many relation between two types, in two different tables
 - SDO_GEOASTER (raster)
 - SDO_RASTER (tile)
 - Only SDO_RASTER is georeferenced
- Supports (too) many raster features for any kind of raster application
 - bitmap mask, two compression schemes, three interleaving types, multiple dimensions, embedded metadata (colour table, statistics, etc...), lots of unimplemented features
- Hard to import
- Designed for raster storage

PostGIS WKT Raster

- Stored as a unique type, in one table
 - RASTER (or tile)
 - Each raster is georeferenced
- Supports the minimal set of characteristics for the geospatial industry
 - georeference, multiband, tiling, pyramids, nodata values
- Easy to import
- Designed for raster/vector analysis

Quelques questions de recherche

- Avec un **API rendant transparentes les opérations d'analyse raster/vector**, comment pouvons-nous **simplifier les interfaces graphiques des SIG** en proposant un **minimum d'opérations?** Quelles devrait être ces opérations?
- Maintenant qu'il est possible de **stocker une couche matricielle discontinue**, comment **modifier** les algorithmes opérants sur des couches matricielles continue pour qu'ils fonctionnent sur ce type de couche?
- Comment pouvons-nous utiliser ces « raster objects » pour **générer des objets aux contours flous?** Quels doivent être les opérations possibles sur ces objets flous?
- Comment pouvons-nous utiliser ces « raster objects » pour mieux **modéliser les objets typiquement matriciels** dans les **systèmes de simulation spatialement explicites?**

Summary

- Lightweight applications (web or desktop) like the **Canadian Spatial Data Foundry** needs server API to manipulate and analyse vector and raster data. When possible, seamlessly. Ideally in SQL.
- **PostGIS WKT Raster** aims to provide such an integration
 - Support for multiband, multiresolution, tiled and non-rectangular raster coverages
 - Seamless operators & functions on raster & vector types
 - Lossless conversion between raster & vector layers
 - **ST_Intersection** and **ST_MapAlgebra** and many others working seamlessly on raster and vector
 - Storage of metadata for raster stored outside the DB
 - Easy import/export similar to PostGIS shp2pgsql
- A new approach to geospatial application development
 - All GIS processes on raster and vector can now be done in the database
- Introduction of a new kind of GIS **raster objects** useful for:
 - modelling categorical features needing raster algorithms
 - or fuzzy objects requiring their own identities

Thanks!

<http://trac.osgeo.org/postgis/wiki/WKTRaster>

